

AN INTEGRATED STATISTICAL VARIANCE AND VIKOR METHODS FOR PRIORITISING POWER GENERATION PROBLEMS IN NIGERIA

I. Emovon^{1*}, O. D. Samuel²

^{1,2}Department of Mechanical Engineering, Federal University of Petroleum Resources, P.M.B 1221, Effurun, Delta State, Nigeria.

ABSTRACT

The bedrock of industrialization of any nation is the supply of adequate and efficient electricity to power both homes and industries. However, electricity supply in Nigeria is grossly inadequate and inefficient, which has resulted in many local industries becoming moribund. The inadequate power supply is mainly due to power generation problems. Some of the problems identified include, among others lack of energy mix, militant activities and corruption. The purpose of this paper is to develop a tool for prioritizing these problems for power generation. Managers able to identify the more critical ones and allocate more resource in addressing them easily. Hence, this paper presents a tool based on the integration of statistical variance and Vlsekriterijumska Optimizacija Ikompromisno Resenje (VIKOR) and compromise solution methods for prioritization of the various problems confronting power generation in Nigeria. The statistical variance method is used in the decision criteria weights determination while the VIKOR method is used in the ranking of power generation problems. The proposed technique was demonstrated with data collected from experts. The result of the analysis showed that the most critical power generation challenge is the poor maintenance of power generation infrastructure.

KEYWORDS: Power generation problems; VIKOR method; statistical variance method; decision criteria

1.0 INTRODUCTION

The key to industrialization of any nation is availability of adequate electricity to power residential buildings and industries. In Nigeria, the bodies entrusted with this responsibility produce electricity, which is grossly inadequate to power homes and industries of the most populous nation in Africa. The erratic and inadequate supply of electricity by these bodies is one of the major reason

* Corresponding Email: emovon.ikuobase@fupre.edu.ng

the nation had remained underdeveloped. Most industries now use individual electricity generators to power their machines, thereby resulting to increase in overhead cost and uncontrolled environmental pollution. Many of the industries had folded up as a result of the ever-increasing overhead cost while some had relocated to other countries.

The government is concerned with the epileptic power supply from the bodies entrusted with the assignment and have carried out various reforms at different times. The various reforms unfortunately had not yielded any positive result. Nigeria remains one of the lowest electricity consumption per capita in African (Olaoye et al., 2016) as shown in Table 1. For example, between the year 2010 and 2014, the electricity consumption per capita in Nigeria was 144 kWh, which was less than half of Ghana and less than five percent of South African electricity consumption per capita (World Bank, 2015). Although the power generation installed capacity is over 25,000 MW, the available capacity is below 5,000 MW as presented in Table 2. Some of the reasons attributed to the gap in the installed capacity and available capacity and in general poor power generation are militant activities, lack of energy mix, high level corruption and poor maintenance culture.

Table 1. Electricity consumption per capita in most African countries (World Bank, 2015)

S/N	Countries	Electric consumption per capita (KWh)
1	Algeria	1,362
2	Angola	344
3	Benin	97
4	Botswana	1,708
5	Cameroon	274
6	Cote d ivoire	281
7	Congo Rep.	213
8	Congo Dem. Rep.	107
9	Egypt	1,699
10	Ethiopia	70
11	Ghana	357
12	Kenya	171
13	Libya	1,841

(continued)

(continued)

14	Morocco	912
15	Mozambique	463
16	Namibia	1,564
17	Niger	52
18	Nigeria	144
19	Senegal	222
20	South Africa	4,229
21	Tanzania	100
22	Tunisia	1,446
23	Zambia	703
24	Zimbabwe	543
25	Sub-Sahara Africa	497

In the literature, different studies on power generation system have been carried by various researchers with respect to improve power generation challenges in Nigeria. Emovon et al. (2011) developed mathematical models for evaluating performance of Egbin thermal power station, Nigeria. Specifically, the models were developed for availability and reliability analysis of power plants. A mathematical model was also proposed for evaluating production losses due to system unavailability. In a similar research, Obodeh (2011) carried out an investigation on the performance of the Sapele thermal power station, Nigeria. Oyedepo et al., (2014) carried out performance and economic analysis of a gas turbine power plant in Nigeria. The performance was evaluated in terms of power outage cost as a result of plant downtime. The study revealed that revenue loss due to system downtime amount to \$251 million. Aliyu (2013) utilized Long-range Energy Alternative Plan (LEAP) to simulate future energy expansion plan in Nigeria. Mohammed (2013) carried out a comprehensive review of four major kinds of renewable energy sources such as biomass, solar, wind and hydro. Adler (1980) presented a mathematical model for evaluating the probability of outages of a power generating plant. Olaoye et al. (2016) carried out investigations on the energy crisis in Nigeria. In the paper, the authors discussed the potentials of renewable energy and the need to harness it to come out of the energy crisis.

From the above review, it is obvious that most of the research in literature mainly dwells on reliability and performance analysis of power generation system. However, in this paper, a tool for prioritizing the various challenges confronting power generation in Nigeria is presented. The tool utilizes a combination of statistical variance method and VIKOR method. The statistical variance method is used in the determination of the weights of decision criteria whilst utilizing the VIKOR method in the ranking of the power generation problems. The tool will assist government and power generation managers in prioritizing power challenges to allocate the bulk of the insufficient resources available for power infrastructure development to the more critical ones for greater power output.

2.0 POWER GENERATION PROBLEMS IN NIGERIA

One of the major barriers to economic growth in Nigeria is the erratic power supply of the bodies entrusted with the generation, transmission and distribution of power. The reason for the erratic supply of electricity to power industrial and residential machines are numerous and diverse. Militant activities have left power generation facilities damaged to pipelines that supply gas to the power station for electricity generation. The Nigerian power sector just like the down stream sector of the oil industry has suffered badly from poor maintenance problem. The power sector, which is regulated by the Power Holding Company of Nigeria (PHCN) has been poorly funded to the extent that many of the power stations are unable to carry out maintenance programs resulting to plant units' ruin (Ayankola, 2009).

To overcome these problems, the three criteria, which are environmental pollution (EP), critical power assets damage (CAD) and power generation output (PGD), are adopted as described in Table 3. They are chosen because each of the power generation problem may result in environmental pollution, critical power asset damage and reduction in power generation output. For example, militant activities such as gas pipeline vandalism can destroy the ecosystem apart from having a negative impact on power generation output. Also, the issue of poor maintenance can cause catastrophic damage to critical power equipment or asset. These criteria are taught to be able to solve the

different problems affecting power generation in Nigeria, as presented in Table 4. The different problems are prioritized based on the three decision criteria.

Table 2. Bodies entrusted with power generation by Government of Nigeria & generation capacity (Olaoye et al., 2016)

S/N	Power generation company	Location	Type	Installed capacity	Capacity available
1	AES Nigeria Barge Ltd		Thermal	270	224
2	Afam Power PLC	Afam, Rivers State	Thermal	987.2	60
3	Agbara Shoreline Power Ltd	Agbara, Ogun State	Thermal	100	
4	Alaoji Generation Company Ltd	Alaoji, Abia State	Thermal	1074	
5	Anita Energy Ltd	Agbara, Lagos State	Thermal	90	
6	Azura Power West Africa Ltd	Ihovor, Benin, Edo state	Thermal	450	
7	Benin Generation Company Ltd	Ihonvor, Edo state	Thermal	450	
8	Calabar Generation Company Ltd	Calabar, Cross River State	Thermal	561	
9	Century Power Generation Ltd	Okija, Anambra State	Thermal	495	
10	Energys Nigeria Ltd	Ado, Ekiti State	Thermal	10	
11	Delta Electric Power Ltd	Oghareki, Delta State	Thermal	116	
12	DIL Power PLC	Obajana, Kogi State	Thermal	135	
13	Egbema Generation Company Ltd	Egbema, Imo State	Thermal	338	
14	Egbin Power PLC	Egbin, Lagos State	Thermal	1320	1100
15	NEGRIS	Ikorodu, Lagos State	Thermal	140	
16	Ethiope Energy Ltd	Ogorode, Delta State	Thermal	2800	300
17	Farm Electric supply Ltd	Ota, Ogun State	Thermal	150	
18	First Independent Power Company Ltd	Omoku, Rivers State	Thermal	150	60
19	First Independent Power Company Ltd	Trans Amadi, Rivers State	Thermal	136	
20	First Independent Power Company Ltd	Eleme, Rivers State	Thermal	95	
21	Fortune Electric Power Company Ltd	Odukpari, Cross River State	Thermal	500	
22	Gbarain Generation Company Ltd	Gbarain, Bayelsa State	Thermal	225	
23	Geometric Power Ltd	Aba, Abia State	Thermal	140	140
24	Geregu Power PLC	Geregu, Kogi State	Thermal	414	276
25	Hudso Power Ltd	Warawa, Ogun State	Thermal	150	
26	Ibafo Power Station	Ibafo, Ogun State	Thermal	200	
27	Ibom Power Ltd	Ikot Abasi, Akwa Ibom State	Thermal	190	

(continued)

(continued)

28	ICS Power Ltd	Alaoji, Abia State	Thermal	624	
29	Isolo Power Generation Ltd	Isolo, Lagos State	Thermal	20	
30	JBS wind power Ltd	Mangu, Plateau State	Wind	100	
31	Kainji Hydro Electric PLC	Kainji, Niger State	Hydro	760	450
32	Kainji Hydro Electric PLC	Jebba, Niger State	Hydro	540	450
33	Knox J and L Energy solution Ltd	Ajaokuta, Kogi State	Thermal	1000	
34	Lotus and Bresson Nigeria Ltd	Magboro, Ogun State	Thermal	60	
35	MBH Ltd	Ikorodu, Lagos State	Thermal	300	
36	Minaj Holdings Ltd	Agu-Amorji, Enugu State	Thermal	115	
37	Nigeria Agip oil Ltd	Okpai, Delta State	Thermal	480	361
38	NESCO	Bukuru, Plateau State	Thermal	30	
39	Notore Power Ltd	Onne, Rivers State	Thermal	50	
40	Ogorode Generation Company Ltd	Ogorode, Delta State	Thermal	450	
41	Olorunsogo Generation Company Ltd	Olorunsogo, Ogun State	Thermal	750	
42	Olorunsogo Power PLC	Olorunsogo, Ogun State	Thermal	335	76
43	Omoku Generation Company Ltd	Omoku, Rivers State	Thermal	250	60
44	Omotosho Generation Company Ltd	Omotosho II, Ondo State	Thermal	500	76
45	Omotosho Power PLC	Omotosho, Ogun State	Thermal	335	35
46	Paras Energy and natural Resources Dev. Ltd	Ogijo, Ogun State	Thermal	96	
47	Sapele Power PLC	Sapele, Delta State	Thermal	1020	90
48	Shell Petroleum Dev. Company Ltd	Afam VI, Rivers State	Thermal	642	450
49	Shiroro Hydro Electric Ltd	Shiroro, Niger State	Hydro	600	450
50	Supertek Electric PLC	Ajaokuta, Kogi State	Thermal	500	
51	Supertek Nigeria PLC	Akwete, Abia State	Thermal	1000	
51	Ughelli Power PLC	Ughelli, Delta State	Thermal	942	320
52	Western Technologies and Energy Services Ltd	Sagamu, Ogun State	Thermal	1000	
53	Zuma Energy Nigeria Ltd (Gas)	Ohaji Egbema, Imo State	Thermal	400	
54	Zuma Nigeria Ltd (Coal)	Itobe, Kogi State	Thermal	1200	
TOTAL				25,255.2	4,978

Table 3. Decision criteria

S/N	Decision criteria	Description
1	Environmental pollution (EP)	Power problems can pollute the environment diversely. For example, militant activities cause physical damages to thermal power station gas pipeline and invariably pollute the environment. The most critical power generation problem is the one whose effect pollute the environment the most
2	Critical power asset damage (CAD)	Equipment for power generation can be damaged due to power problems and the one with the greater effect is the most critical
3	Power generation output (PGO)	Power generation can be hampered by power problems, thereby resulting in reduction in generated power. The problem that will impact more negatively is the most critical

Table 4. Power generation problems

S/N	Power generation problem	Description
1	Poor maintenance	The right maintenance approach not being utilized for maintenance of power generation equipment's. They react to failure in most cases rather than being proactive
2	Corruption	Power generation managers mismanage resources allocated for power improvement
3	Inadequate funding	Inadequate fund to purchase modern equipment and maintain existing infrastructure
4	Militant activities	Pipeline which supply gas to most thermal power station is deliberately being vandalized by Militant
5	Inadequate manpower	Technical manpower for operating and maintenance of power equipment at optimal level is either lacking or inadequate.
6	Wrong location	Location of power station far from sources of human capacity and energy due to nepotism and ethnicity
7	Drought	Little or no rain which adversely affect hydro power generation
8	Poor electricity pricing	Electricity customers' inability to pay for the actual value of electricity due to poverty forcing power distributors to charge less.
9	Lack of policy continuity	Different successive Government coming on board with different policies instead of building on good policy of their predecessors.

3.0 METHODOLOGY

3.1 Criteria weighting tool: Statistical variance method

Criteria weighting is an important factor in prioritizing power generation problems because of its impact in the final ranking of the different power problems. In the literature, many approaches have been applied in evaluating weights of criteria. The application of an objective technique such as the statistical variance method has been reported in literature (Rao & Patel, 2010; Nirmal, 2013). A subjective technique such as Analytic Hierarchy Process (AHP) and Points method have also been applied (Rao, 2008). The statistical variance method was chosen in this paper because it is an objective method of criteria weights determination, thereby reducing personal bias in the overall decision making process.

The variance method steps are as follows (Rao and Patel, 2010):

1. Formation of the decision matrix.

The decision matrix is formed as shown in Equation (1):

$$P = (\bar{p}_{ij})_{m.n} \quad (1)$$

2. The decision matrix normalization.

The normalization of the decision matrix is as given in Equation (2):

$$y_{ij} = \frac{\bar{p}_{ij}}{\sum_{i=1}^m \bar{p}_{ij}}, \quad i = 1, 2, \dots, m; \quad j = 1, 2, \dots, n \quad (2)$$

where y_{ij} is the normalized matrix.

3. The variance of each risk criterion is evaluated as given in Equation (3):

$$V_j = \frac{1}{m} \left[\sum_i^m (y_{ij} - \bar{y}_{ij})^2 \right] \quad (3)$$

where \bar{y}_{ij} is the mean value of y_{ij} and V_j is the variance of each risk criterion.

4. The weight of each decision criterion is evaluated as given in Equation (4):

$$w_j = \frac{V_j}{\sum_j^n V_j} \quad (4)$$

where w_j is the weight of each criterion.

3.2 Ranking tool: VIKOR Method

The VIKOR method is a multi-criteria decision making tool which selects a compromise solution from a set of options with reference to decision criteria. The compromise solution is attained using a ranking index based on a measure of closeness to the positive ideal solution. The technique was developed in 1979 by Opricovic (1998). The VIKOR method has been applied in solving various multi-criteria decision making problems by some authors (Liu et al., 2013 ; Chatterjee et al., 2009 ; Rao, 2008 ; Çalışkan et al., 2013 ; Anojkumar et al., 2014). Other description of the VIKOR method can be referred to the work by Opricovic (1998) and Opricovic & Tzeng (2004).

The VIKOR methodology steps are as follow (Çalışkan et al., 2013, Emovon, et al, 2015):

1. Determination of the best and worst values for each criterion.

With reference to the decision matrix in Equation (5), the best and worst values for each criterion are determined as:

$$\bar{p}_j^+ = \max_i \bar{p}_{ij}, \quad \bar{p}_j^- = \min_i \bar{p}_{ij} \quad (5)$$

where, \bar{p}_j^+ is the best value for the j^{th} criterion, and \bar{p}_j^- is the worst value for the j^{th} criterion.

2. Evaluation of the utility measure and regret measure for each power generation problem is as given in Equations (6) and (7):

$$S_i = \sum_{j=1}^n w_j (\bar{p}_j^+ - \bar{p}_{ij}) / (\bar{p}_j^+ - \bar{p}_j^-) \quad (6)$$

$$R_i = \max_j \left[w_j (\bar{p}_j^+ - \bar{p}_{ij}) / (\bar{p}_j^+ - \bar{p}_j^-) \right] \quad (7)$$

where

w_j is the weight of j^{th} criterion

S_i is the utility measure

R_i is the regret measure

3. Calculation of the VIKOR index value Q_i , as given in Equation (8):

$$Q_i = v(S_i - S^+) / (S^- - S^+) + (1 - v)(R_i - R^+) / (R^- - R^+) \quad (8)$$

where

$$S^+ = \max_i [(S_i), \quad i = 1, 2, \dots, m]$$

$$S^- = \min_i [(S_i), \quad i = 1, 2, \dots, m]$$

$$R^+ = \max_i [(R_i), \quad i = 1, 2, \dots, m]$$

$$R^- = \min_i [(R_i), \quad i = 1, 2, \dots, m]$$

v represents the weight of the decision-making strategy of the maximum group utility whose values varies from 0 to 1. If v is set at 1, it is a decision-making process that utilizes a strategy of maximum group utility and if set at 0, a decision-making process that utilizes a strategy of minimum regret (Kuo et al., 2015). In this paper, v is set at 0.5 because it is generally set at this value according to (Çalışkan et al., 2013) and this is due to the fact that most decision making process involves both maximum group utility and individual regret (Kuo et al., 2015).

4. The ranking of power generation problems is based on the VIKOR index value, Q_i , and the smaller the value the better the rank.

4.0 DATA COLLECTION AND ANALYSIS

4.1 Data collection

Data for evaluating and prioritizing the power generation problems with respect to three decision criteria were obtained using experts' opinions. Two experts rated the power generation problems utilizing a questionnaire developed based on 5-point Likert scale. The individual experts' rating was averaged and results are presented in Table 5. The information in Table 5 were then applied as input data into the VIKOR method for the final ranking of the power generation problems.

Table 5. Expert average rating of power generation problems (decision matrix)

S/N	Power generation problems	EP	CAD	PGO
1	Poor maintenance	2.5	5	5
2	Corruption	2	3	5
3	Inadequate funding	2.5	3.5	4
4	Militant activities	4	3.5	4
5	Inadequate manpower	3	3	3
6	Wrong location	3	2	3
7	Drought	1	1	2
8	Poor pricing of electricity	2	2.5	1.5
9	Lack of policy continuity	1.5	3	3

4.2 Data Analysis

4.2.1 Decision criteria weights determination

Having obtained the decision matrix in Table 5, the next step was to determine the weights of decision criteria. To achieve this aim, firstly, the decision matrix was normalized using Equation (2) and the results are presented in Table 6. Following this, the statistical variance of each decision criterion was evaluated using Equation (3) on information in Table 6. Finally, the weight of each decision criterion was evaluated using Equation (4) and the results are presented in Table 7.

Table 6. Normalized decision matrix

Power generation problem	EP	CAD	PGO
1	0.5392	1.0783	1.0783
2	0.4313	0.5828	0.9054
3	0.5392	0.6799	0.7243
4	0.8627	0.6799	0.7243
5	0.6470	0.5828	0.5432
6	0.6470	0.3885	0.5432
7	0.2157	0.1943	0.3621
8	0.4313	0.4856	0.2716
9	0.3235	0.5828	0.5432

Table 7. Decision criteria weights

Decision criteria	Weights
EP	0.2477
CAD	0.3455
PGO	0.4068

4.2.2 Ranking of power generation problems.

The weights of EP, CAD and PGO obtained in Section 4.2.1 together with the decision matrix in Table 5 were then applied as input data for the VIKOR technique for the final ranking of power generation problems. The first step in the VIKOR analysis was the determination of the best and worst values for each criterion which was achieved by applying Equation (5) to the decision matrix in Table 5. The results obtained are presented in Table 8. The utility and regret measure for each power generation problems were then evaluated using Equations (6) and (7) respectively, and results are presented in Table 9. Finally, based on which power generation problems, VIKOR index is ranked, using Equation (8) on Table 9 and the results are presented in Table 10.

Table 8. Best and worst value

Decision criteria	Worst value	Best value
EP	1	4
CAD	1	5
PGO	1.5	5

Table 9. Regret measure, utility measure and VIKOR index

S/N	Power generation problems	Si	Ri
1	Poor maintenance	0.0000	0.0000
2	Corruption	0.1382	0.1103
3	Inadequate funding	0.1493	0.0129
4	Militant activities	0.0693	0.0129
5	Inadequate manpower	0.2162	0.1794
6	Wrong location	0.2719	0.3051
7	Drought	0.5000	0.5000
8	Poor pricing of electricity	0.5237	0.5237
9	Lack of policy continuity	0.1861	0.1861

Table 10. Power generation problem VIKOR index and rank

S/N	Power generation problems	Q_i	Rank Q_i
1	Poor maintenance	0.0000	1
2	Corruption	0.2485	4
3	Inadequate funding	0.1621	3
4	Militant activities	0.0822	2
5	Inadequate manpower	0.3956	5
6	Wrong location	0.5770	7
7	Drought	1.0000	9
8	Poor pricing of electricity	0.9196	8
9	Lack of policy continuity	0.4823	6

From Table 10, it is obvious that the most critical challenge confronting power generation in Nigeria is the poor maintenance of power infrastructure having the lowest VIKOR index of 0. Militant activities are ranked second with a VIKOR index of 0.0822 and as such the second most critical challenge confronting power generation. The last challenge is the problem of drought having rank in the last position. The tool utilized in the ranking of power generation problems requires less computational effort than similar Multi-Criteria Decision Making (MCDM) tools such as the TOPSIS method (Nirmal, 2013; Rao, 2008 ; Carpinelli et al., 2014). Moreover, the limitation of the MCDM tool such as TOPSIS technique which has inability to consider the relative distance from the positive ideal and negative ideal solutions may be addressed through the VIKOR method (Anojkumar et al., 2014).

5.0 CONCLUSION

The inadequate and erratic supply of electricity to residential home and industries is the main reason Nigeria is grossly underdeveloped. Despite concerted effort made by successive government to reverse this ugly trend, Nigeria is still one of the lowest electricity consumptions per capita in Africa. In this research, a tool for prioritizing the various problems affecting the power generation in Nigeria is presented. The tool uses an integrated statistical variance method and VIKOR method for the ranking of different power generation problems based on three decision criteria. To demonstrate the suitability of the tool, data were obtained via expert opinion and analyzed. The result of the analysis revealed that poor maintenance of power equipment is the most critical problem confronting power generation in Nigeria. This research will stimulate Federal Government of Nigeria as a matter of urgency to declare a state of emergency with respect to proactive maintenance of power generation infrastructure across the Country. The proposed tool will also be useful to other nations in prioritizing power generation problems and other related challenges.

ACKNOWLEDGEMENT

The authors are grateful to the Federal University of Petroleum Resources, Nigeria for the technical support of this research work.

REFERENCES

- Adler, H. A. (1980). Pricess and method of calculation of probability of loss generating capacity, *IEEE Trasaction on Power apparatus and systems*, 86: 11
- Aliyu, A.S., Ramli, A.T. & Saleh, M.A. (2013). Nigeria electricity crisis: Power generation capacity expansion and environmental ramifications. *Energy*, 61: 354-367.
- Anojkumar, L., Ilangkumaran, M. & Sasirekha, V. (2014). Comparative analysis of MCDM methods for pipe material selection in sugar industry. *Expert Systems with Applications*, 41: 2964-2980.
- Ayankola, M. (2009). Sapele power station resumes operation, *The Punch*, 2nd October: 17.

- Çalışkan, H., Kurşuncu, B., Kurbanoglu, C. & Güven, T. Y. (2013). Material selection for the tool holder working under hard milling conditions using different multi criteria decision making methods. *Materials and Design*, 45: 473-479.
- Chatterjee, P., Athawale, V. M. & Chakraborty, S. (2009). Selection of materials using compromise ranking and outranking methods. *Materials & Design*, 30: 4043-4053.
- Carpinelli, G., Caramia, P., Mottola, F. & Proto, D. (2014). Exponential weighted method and a compromise programming method for multi-objective operation of plug-in vehicle aggregators in microgrids. *International Journal of Electrical Power & Energy Systems*, 56: 374-384.
- Emovon, I., Kareem B., Adeyeri, M.K. (2011). Performance evaluation of Egbin Thermal Power Station, Nigeria. In *Proceedings of the world congress on engineering and computer science, California, United States*, 19-21.
- Emovon I, Norman RA, Murphy AJ, Pazouki K. (2015). An integrated multicriteria decision making methodology using compromise solution methods for prioritising risk of marine machinery systems. *Ocean Engineering* 105: 92-103.
- Kuo, T.C., Hsu, C.W. & Li, J.Y., (2015). Developing a green supplier selection model by using the DANP with VIKOR. *Sustainability*, 7(2): 1661-1689.
- Liu, H.-C., Mao, L.-X., Zhang, Z.-Y. & Li, P. (2013). Induced aggregation operators in the VIKOR method and its application in material selection, *Applied Mathematical Modelling*, 37: 6325-6338.
- Mohammed, Y.S., Mustafa, M.W., Bashir, N. & Mokhtar, A.S. (2013). Renewable energy resources for distributed power generation in Nigeria: a review of the potential. *Renewable and Sustainable Energy Reviews*, 22: 257-268.
- Nirmal, P. (2013). A comparative Analysis of TOPSIS and VIKOR Methods in the Selection of Industrial Robots. B. Tech. Undergraduate, National Institute of Technology.
- Obodeh, O. & Isaac, F.O. (2011). Performance analysis for Sapele thermal power station: case study of Nigeria. *Journal of Emerging Trends in Engineering and Applied Sciences*, 2(1): 166-171.
- Olaoye, T., Ajilore, T., Akinluwade, K., Omole, F. and Adetunji, A. (2016). Energy crisis in Nigeria: Need for renewable energy mix, *American Journal of Electrical Electronics Engineering*, (4)1: 1-8.

- Opricovic, S. (1998). *Multicriteria Optimization of Civil Engineering Systems*. Faculty of Civil Engineering, Belgrade.
- Opricovic, S. & Tzeng, G. H. (2004). Compromise solution by MCDM methods: A comparative analysis of VIKOR and TOPSIS. *European Journal of Operational Research*, 156: 445-455.
- Oyedepo, S.O., Fagbenle, R.O., Adefila, S.S. and Adavbiele, S.A. (2014). Performance evaluation and economic analysis of a gas turbine power plant in Nigeria, *Energy Conversion and Management*, 79: 431-440.
- Rao, R. V. (2008). A decision making methodology for material selection using an improved compromise ranking method. *Materials & Design*, 29: 1949-1954.
- Rao, R. V. & Patel, B. K. (2010). A subjective and objective integrated multiple attribute decision making method for material selection. *Materials & Design*, 31: 4738-4747.
- World Bank (2015). *Electric power consumption (KWh per capita)*, Retrieved from <http://www.data.worldbank.org/indicator/EG.USE.ELEC.KH.PC>